









DIGITAL TWIN TIMER 數位型雙調型限時繼電器

| SPECIFICATION 規格 | | TDV-NM | TDV-YM | TDV-NDM | TDV-YDM |
|-------------------------------|------------------|---|---|--|---|
| Model 型號 | |  |  |  |  |
| Dimension(mm) 尺寸 | | 61H*49W*70D | 88H*58W*68D | 61H*49W*70D | 88H*58W*68D |
| Time Range 時間範圍 | | x.01Sec, x0.1Sec, x1Sec, x.59Sec x0.1Min, x1Min, x.59Min x0.1Hr, x1Hr, x10Hr | | | |
| Supply Voltage 額定電壓 | | DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz | | | |
| Contact Rating 接點容量 | | 250VAC 5A Resistive Load 48VDC 5A 電阻性負載 | | | |
| Reset Time 復歸時間 | | 0.1 sec max | | | |
| Consumed Power 消耗功率 | | 3VA | | | |
| Ambient Temperature 使用周圍溫度 | | -10°C~+55°C | | | |
| Ambient Humidity 使用周圍濕度 | | 45~85%RH | | | |
| Life 壽命 | Mechanical 機械 | 5×10 ⁶ times | | | |
| | Electrical 電氣 | 10 ⁵ times | | | |
| Weight 重量 | | 210g | | | |
| Connection 接線圖 | | <p>限時2C</p>  <p>mode A</p> | | <p>限時1C, 瞬時1C</p>  <p>mode B</p> | |
| Timing Chart 時序圖 | |  | |  | |